


GOT-3840TL

8.4" SVGA TFT Cost-effective Fanless Touch Panel Computer




- | | | |
|--|---------------------|-----------------|
| 1. Power switch | 4. Audio (Line-out) | 7. PS/2 K/B/M/S |
| 2. DC inlet | 5. USB 2.0 x 2 | 8. Ethernet |
| 3. COM 1/2/3
(RS-232/422/485, RS-232) | 6. Ethernet | 9. VGA |



Features

- 8.4" SVGA (800 x 600) color TFT LCD display
- Fanless cooling system with low power AMD Geode LX800 500 MHz processor
- Supports Dual LAN & WLAN antenna
- Compact design for space-limited application
- Supports anti-vibration up to 1.3G (HDD, random)
- Supports panel mount, wall mount, VESA arm, desktop stand (optional)



Rear view

Introduction

The GOT-3840TL is a 8.4" fanless touch panel computer. Integrated with 8.4" TFT LCD and AMD Geode LX800 500 MHz processor, the GOT-3840TL provides customers the most economical solution. With the compact design, the GOT-3840TL is ideal for space-limited environments, such as industrial machinery and transportations. In response to the growing demand for WLAN application, the GOT-3840TL also supports optional WLAN antenna for wireless network connection. The GOT-3840TL can be used extensively for various applications including industrial machinery, processing status monitoring, and more.

Cost-effective solution

Integrated with 250 nits LCD and onboard AMD Geode LX800 500 MHz processor, the GOT-3840TL provides an economical solution for customers in response to demands for cost-effective product.

WLAN antenna supported (optional) and Dual-LAN

The GOT-3840TL provides a MiniPCI slot and an optional fixed rotational WLAN

antenna for wireless network connections. By simply plugging in the WLAN card, customer can operate the GOT-3840TL in a wireless environment. Besides, the GOT-3840TL also supports Dual-LAN function for the growing demands of LAN connection.

Compact design for space-limited application

The GOT-3840TL is specially designed for space-limited applications including industrial machinery, transportation and home automation. This fanless touch computer is designed around the concept of small cut-out dimension. Moreover, the GOT-3840TL adopts sleek appearance and streamlined mechanical layout.

Anti-vibration up to 1.3G


With a special vibration-resistant design patent, the GOT-3840TL can work well under 1.3G (5-500Hz) in operation mode, and equipped with a 2.5" HDD.

Specifications

Front Bezel	IP65, NEMA 4 rugged protection, aluminum front bezel		BIOS	Award 4Mbit with RPL/PXE LAN boot ROM, Smartview and customer CMOS backup	
LCD Panel	Display Type	8.4" SVGA TFT LCD	Storage	1 x 2.5" IDE HDD	
	Brightness (cd/m ²)	250 nits		1 x CompactFlash™	
	Resolution	800 x 600		Watchdog	255 levels, 0-255 sec.
	Viewing Angle (H/V)	160° / 140°			Timer
Main System	CPU	AMD Geode LX800 500 MHz	Onboard	Integrated in AMD LX chipset	
	Chipset	AMD LX + CS5536AD + ITE8888G	Graphics		
	System Memory	1 x 200-pin DDR SO-DIMM max. up to 1 GB			

I/O Connector	2 x RS-232(COM 2/3) 1 x RS-232/422/485 (COM 1) 1 x VGA 1 x Audio (Line-out) 1 x PS/2 keyboard/mouse 2 x USB 2.0 2 x 10/100Mbps Ethernet
Expansion Interface	1 x MiniPCI slot 1 x PC/104 slot
Touchscreen	Resistive type
Power Supply	16-28V _{DC} , 48W, w/ fuse power protection
Dimensions	280 mm (11.02") (W) x 69.3 mm (2.73") (D) x 200 mm (7.87") (H)
Packing Dimensions	380 mm (14.96") (W) x 190 mm (7.48") (D) x 440 mm (17.32") (H)
Weight (net/gross)	3.5 kg (7.7 lb)/4.2 kg (9.26 lb)
Environment	Operating temperature: 0°C - +50°C (32° - 122°F) Relative humidity: 10% - 95% @ 40°C; non-condensing Operation vibration: 1.3G, 5 - 500Hz, random for 2.5"HDD 2.0G, 5 - 500Hz, random for CompactFlash™
Certification	CE

Dimensions



Ordering Information

GOT-3840TL	8.4" SVGA TFT cost-effective fanless touch panel computer
82238400800E	Wall/VESA kit for GOT-3840TL
82018400060E	Desktop stand kit for GOT-3840TL
50966A23040E	Power adapter, 70W, 110-230V _{AC} to 24V _{DC}
E201840102	Metal cover for 1 PC/104 slot
E201840101	Metal cover for 2 PC/104 slot
E392203100	802.11 b/g wireless LAN kit

* Specification and certifications are based on options and may vary.

Optional EOS Installation

Windows® XP Embedded
Windows® CE.NET

Optional OS Installation

Windows® XP

Overview

Industrial Panel Computers & Monitors

Heavy-duty Fanless Touch Panel Computers

Digital Signage Solutions

Healthcare & Medical Solutions

Open Frame Panel Computers

Accessories