

MiniPCI-WLAN-Card USB Wireless LAN module

MiniPCI WLAN Module



Specifications

Chipset	VIA VT6655 Wireless LAN Controller
Bus	Mini-PCI standard compliant
Frequency Band	2400-2483.5MHz (for US, Canada) 2400-2483.5MHz (for Europe) 2400-2497MHz (for Japan)
Operating Channel	IEEE 802.1b, Direct Sequence Spread Spectrum, IEEE 802.11g, Orthogonal Frequency Division Multiplexing 11 Channels (US, Canada) 13 Channels (Europe and Japan)
Driver Support	Windows: 98SE/Me/NT/2000/XP/2003 Ser., Linux (2.4.x/2.6.x), CE (4.2/5.0/6.0) Linux source code available on website
Power consumption	802.11b: 250 mA @ 3.3V, 802.11g: 230mA @ 3.3V Listening: 190mA @ 3.3V
Weight	20g
Board Size	64.7 x 44.6 x 3.8mm
Operating Temperature	0°C ~ +55°C
Compliance Certifications	CE/FCC/Wi-Fi/NCC/Telec/Singapore

Packing List

- MINI-PCI-WLAN-CARD x1
- WIRELESS-ANTENNA x1 (Optional)
- WIRELESS-CABLE-150MM x1 (Optional)



Specifications

Chipset	VIA VT6656 Wireless LAN Controller
Bus	USB standard compliant
Frequency Band	2400-2483.5MHz (for US, Canada) 2400-2483.5MHz (for Europe) 2400-2497MHz (for Japan)
Operating Channel	IEEE 802.1b, Direct Sequence Spread Spectrum, IEEE 802.11g, Orthogonal Frequency Division Multiplexing 11 Channels (US, Canada) 13 Channels (Europe and Japan)
Driver Support	Windows: 98SE/Me/NT/2000/XP/2003 Ser., Linux (2.4.x/2.6.x), CE (4.2/5.0/6.0) Linux source code available on website
Power consumption	802.11b: 250 mA @ 3.3V, 802.11g: 230mA @ 3.3V Listening: 190mA @ 3.3V
Weight	10g
Board Size	25 x 60 x 5.9mm
Operating Temperature	0°C ~ +55°C
Compliance Certifications	CE/FCC/Wi-Fi/NCC/Telec/Singapore

Packing List

- USB-WLAN-MODULE x1
- WIRELESS-CABLE-150MM x1 (Optional)
- WIRELESS-ANTENNA x1 (Optional)
- CABLE-WLAN-30M (2.0) x1 (Optional)
- CABLE-WLAN-30M (2.54) x1 (Optional)
- CABLE-USB-WLAN-30CM x1 (Optional)