



FCC 47 CFR PART 15 SUBPART B

Product Type : ICP DAS with Converter
Applicant : ICP DAS CO., LTD.
Address : No. 111, Kuangfu N. Rd., Hukon Shiang, Hsinchu, Taiwan 303, R.O.C
Trade Name : ICP DAS
Model Number : LP-8781-Atom
Test Specification : FCC 47 CFR PART 15 SUBPART B: Oct., 2012
ANSI C63.4: 2009
Receive Date : Oct. 25, 2013
Test Period : Nov. 01 ~ 04, 2013
Issue Date : Nov. 14, 2013

Issue by

A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade City,
Taoyuan County 334, Taiwan R.O.C.
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330

Note: This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. This document may be altered or revised by A Test Lab Techno Corp. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, or any government agencies. The test results in the report only apply to the tested sample.

Verification of Compliance

Issued Date: 2013/11/14

Product Type : ICP DAS with Converter
Applicant : ICP DAS CO., LTD.
Address : No. 111, Kuangfu N. Rd., Hukon Shiang, Hsinchu, Taiwan 303, R.O.C
Trade Name : ICP DAS
Model Number : LP-8781-Atom
EUT Rated Voltage : AC 100-250V, 50-60Hz, 2.0A
Test Voltage : 120 Vac / 60 Hz
Applicable : FCC 47 CFR PART 15 SUBPART B: Oct., 2012
Standard : ANSI C63.4: 2009
 CISPR 22: 2009+A1: 2010
Test Result : Complied
Performing Lab. : A Test Lab Techno Corp.

No. 140-1, Changan Street, Bade City,
Taoyuan County 334, Taiwan R.O.C.

Tel : +886-3-2710188 / Fax : +886-3-2710190

Taiwan Accreditation Foundation accreditation number: 1330

<http://www.atl-lab.com.tw/e-index.htm>



The above equipment has been tested by A Test Lab Techno Corp., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved By : Cran Yang Reviewed By : Frank Lin
(Manager) (Cran Yang) (Testing Engineer) (Frank Lin)

Feature of Equipment under Test :

The model listed below is series model to LP-8781-Atom.

Main	OS	Diversity	Mode 1
LP-8081-EN	Linux	Standard LinPAC-8000 with 0 I/O slots (English version of OS)	
LP-8381-EN	Linux	Standard LinPAC-8000 with 3 I/O slots (English version of OS)	
LP-8781-EN	Linux	Standard LinPAC-8000 with 7 I/O slots (English version of OS)	V
LP-8141-EN	Linux	Standard LinPAC-8000 with 1 I/O Slot (English Version of OS)	
LP-8441-EN	Linux	Standard LinPAC-8000 with 4 I/O Slots (English Version of OS)	
LP-8841-EN	Linux	Standard LinPAC-8000 with 8 I/O Slots (English Version of OS)	
LP-8131-EN	Linux	Standard LinPAC-8000 with 1 I/O Slot (English Version of OS)	
LP-8431-EN	Linux	Standard LinPAC-8000 with 4 I/O Slots (English Version of OS)	
LP-8831-EN	Linux	Standard LinPAC-8000 with 8 I/O Slots (English Version of OS)	
LP-8181-Atom	Linux	Standard LinPAC-8000-Atom with 1 I/O Slot (Multilingual Version of OS) (RoHS)	
LP-8381-Atom	Linux	Standard LinPAC-8000-Atom with 3 I/O Slot (Multilingual Version of OS) (RoHS)	
LP-8781-Atom	Linux	Standard LinPAC-8000-Atom with 7 I/O Slot (Multilingual Version of OS) (RoHS)	V
I-8112iW	---	2-port Isolated RS-232 Module (RoHS)	V
I-8114iW	---	4-port Isolated RS-232 Module (RoHS)	V
I-8114iW/D2	---	4-port Isolated RS-232 Module (RoHS)	
I-87013W	---	4-channel RTD Input Module (Gray Cover) (RoHS)	V
I-87017RW	---	8-channel Analog Input Module (Gray Cover) (RoHS)	V
I-87017RCW	---	8-channel Current Input Module (Gray Cover) (RoHS)	
I-87053W	---	16-channel Isolated Digital Input Module with 16-bit Counters (Gray Cover) (RoHS)	V
I-87053PW	---	16-channel Isolated Digital Input Module with 16-bit Counters (Gray Cover) (RoHS)	
I-87053W-A2	---	16-channel Isolated Digital Input Module with 16-bit Counters (Gray Cover) (RoHS)	
I-87053W-A5	---	16-channel 68-150 VDC Isolated Digital Input Module with 16-bit Counters (Gray Cover) (RoHS)	
I-87053W-E5	---	16-channel 68-150 VDC Isolated Digital Input Module with 16-bit Counters (Gray Cover) (RoHS)	
I-87053W-AC1	---	16-channel AC Isolated Digital Input Module with 16-bit Counters (Gray Cover) (RoHS)	
I-8060W	---	6-channel Relay Output Module (Gray Cover) (RoHS)	V
I-8068W	---	4-channel Form-A Relay Output and 4-channel Form-C Relay Output Module (Gray Cover) (RoHS)	V
I-87061W	---	16-channel Relay Output Module (Gray Cover) (RoHS)	V

Main	Software	Diversity	Mode 1
I-8053PW	---	16-channel Isolated Digital Input with Low Pass Filter Module (Gray Cover) (RoHS)	V
I-8058W	---	8-channel 80-250VAC Isolated Digital Input Module (Gray Cover) (RoHS)	V
I-8051W	---	16-channel Non-isolation Digital Input Module (Gray Cover) (RoHS)	V
I-8057W	---	16-channel Isolated Open Collector Output Module (Gray Cover) (RoHS)	V
I-8069W	---	8-channel PhotoMOS Relay Output Module (Gray Cover) (RoHS)	V
I-8144iW	---	4-port Isolated RS-422/485 Module (RoHS)	V
I-8142iW	---	4-port Isolated RS-422/485 Module (RoHS)	
DB-37	---	Direct Connection Board (RoHS)	V
NS-205FT	---	Multi-mode, ST Connector, 4-port 10/100 Mbps with 1 fiber port Switch (RoHS)	
NS-205FC	---	Multi-mode, SC Connector, 4-port 10/100 Mbps with 1 fiber port Switch (RoHS)	
NS-205FCS	---	Single-mode 15 km, SC Connector, 4-port 10/100 Mbps with 1 fiber port Switch (RoHS)	V
NSM-205FT	---	Multi-mode, ST Connector, 4-port 10/100 Mbps with 1 fiber port Switch; metal case (RoHS)	
NSM-205FC	---	Multi-mode, SC Connector, 4-port 10/100 Mbps with 1 fiber port Switch; metal case (RoHS)	
NSM-205FCS	---	Single-mode 15 km, SC Connector, 4-port 10/100 Mbps with 1 fiber port Switch; metal case (RoHS)	V
IDS-7020	---	Programmable Device Server with 1 RS-232, 1 RS-485	V
IDS-7052	---	Programmable Device Server with 4 RS-232, 1 RS-485	
IDS-7058	---	Programmable Device Server with 3 RS-232, 1 RS-485, 1 RS-422/485	