



FCC 47 CFR PART 15 SUBPART B

Product Type : ICP DAS Controller IO Devices
Applicant : ICP DAS CO., LTD.
Address : No. 111, Guangfu N. Rd., Hukou Township, Hsinchu County 30351,
Taiwan, R.O.C.
Trade Name : ICP DAS
Model Number : TP-6150
Test Specification : FCC 47 CFR PART 15 SUBPART B: Oct., 2012
ANSI C63.4: 2009
CISPR 22: 2008
Receive Date : Jun. 30, 2014
Test Period : Jul. 08, 2014
Issue Date : Aug. 04, 2014

Issue by

A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade City,
Taoyuan County 334, Taiwan R.O.C.
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330

Note: This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. This document may be altered or revised by A Test Lab Techno Corp. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, or any government agencies. The test results in the report only apply to the tested sample.

Verification of Compliance

Issued Date: 2014/08/04

Product Type : ICP DAS Controller IO Devices

Applicant : ICP DAS CO., LTD.

Address : No. 111, Guangfu N. Rd., Hukou Township, Hsinchu County
30351, Taiwan, R.O.C.

Trade Name : ICP DAS

Model Number : TP-6150

EUT Rated Voltage : AC 100-250V, 50/60Hz, 2.0A

Test Voltage : 120 Vac / 60 Hz



Applicable : FCC 47 CFR PART 15 SUBPART B: Oct., 2012
Standard ANSI C63.4: 2009
CISPR 22: 2008

Test Result : Complied

Performing Lab. : A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade City,
Taoyuan County 334, Taiwan R.O.C.
Tel : +886-3-2710188 / Fax : +886-3-2710190
Taiwan Accreditation Foundation accreditation number: 1330
<http://www.atl-lab.com.tw/e-index.htm>



The above equipment has been tested by A Test Lab Techno Corp., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved By :  Reviewed By : 

(Manager) (Roy Chen) (Testing Engineer) (Frank Lin)

2 EUT Description

Product Type	:	ICP DAS Controller IO Devices
Trade Name	:	ICP DAS
Model Number	:	TP-6150
Applicant	:	ICP DAS CO., LTD. No. 111, Guangfu N. Rd., Hukou Township, Hsinchu County 30351, Taiwan, R.O.C.
Manufacturer	:	ICP DAS CO., LTD. No. 111, Guangfu N. Rd., Hukou Township, Hsinchu County 30351, Taiwan, R.O.C.

I/O Port Description :

I/O Port Types	Q'TY	Test Description
1). DC Power Port	1	Connected to EUT
2). LAN Port	1	Connected to EUT
3). USB Port	1	Connected to EUT
4). AC Power Port	1	Connected to AC input

Feature of Equipment under Test :

The model listed below is series model to TP-6150.

Main	Software	Diversity	Mode 1
CAN-2019C	---	CANopen Slave Module of 10-channel Universal Analog Input Include CAN-2019C module	V
CAN-2019C/S	---	CANopen Slave Module of 10-channel Universal Analog Input Include CAN-2019C module and a DB-1820 daughter board	
CAN-2019C/S2	---	CANopen Slave Module of 10-channel Universal Analog Input Include CAN-2019C module, a DB-1822 daughter board and a 1.8m Cable	
CAN-2026C	---	CANopen slave module with 6-channel AI, 2-channel AO, 1-channel DO and 2-channel DI	V
I-7005	---	8-channel Thermistor Input and 6 channel Alarm Output Module	V
I-7005-X	---	8-channel Thermistor Input and 6 channel Alarm Output Module (X:The Cover is mean any color)	
M-7005	---	8-channel Thermistor Input and 6 channel Alarm Output Module	
M-7005-X	---	8-channel Thermistor Input and 6 channel Alarm Output Module (X:The Cover is mean any color)	
I-7011	---	One-channel Thermocouple Input Module	
I-7011D	---	One-channel Thermocouple Input Module with LED Display	V
M-7011	---	One-channel Thermocouple Input Module	
M-7011D	---	One-channel Thermocouple Input Module with LED Display	
I-7011P	---	One-channel Thermocouple Input Module	
I-7011PD	---	One-channel Thermocouple Input Module with Display	V
I-7014D	---	Analog Transmitter Input with LED Display	V
I-7188EX-MTCP	MiniOS7	I-7188EX with default Modbus/TCP firmware	
I-7188EXD-MTCP	MiniOS7	I-7188EXD with default Modbus/TCP firmware	
I-7188EX	MiniOS7	I-7188EXD without display	
I-7188EXD	MiniOS7	Embedded controller with 7-segment display, developing tool kit, 512K bytes flash, 512K bytes SRAM and MiniOS7.	V
I-7188E8	MiniOS7	I-7188E8D without LED display	
I-7188E8D	MiniOS7	Internet communication controller with seven RS-232, one RS-485 and one Ethernet	V
I-7188E4	MiniOS7	I-7188E4D without LED display	
I-7188E4D	MiniOS7	Internet communication controller with three RS-232, one RS-485 and one Ethernet	V
I-7188E5-485	MiniOS7	Internet Communication Controller	
I-7188E5D-485	MiniOS7	I-7188E5-485 with seven-segment display	
I-7188E5	MiniOS7	I-7188E5D without LED display	V
I-7188E5D	MiniOS7	Internet communication controller with four RS-232, one RS-485 and one Ethernet	
I-7188E1	MiniOS7	I-7188E1D without LED display	

Main	Software	Diversity	Mode 1
I-7188E1D	MiniOS7	Ethernet to RS-232 converter	V
I-7188E3-232	MiniOS7	I-7188E3D-232 without LED display	
I-7188E3D-232	MiniOS7	Internet communication controller with two RS-232, one RS-485 and one Ethernet	V
I-7188	MiniOS7	Embedded controller includes 512K flash, MiniOS7, download utility, download cable and manual.	
I-7188D	MiniOS7	Embedded controller includes 512K flash, 5 digits seven segment display, MiniOS7, 5 digits seven segment display, download utility, download cable and manual.	V
I-7188/DOS/512	ROM-DOS	Embedded controller includes 512K flash, ROM-DOS, download utility, download cable and manual.	
I-7188D/DOS/512	ROM-DOS	Embedded controller includes 512K flash, 5 digits seven segment display, ROM-DOS, 5 digits seven segment display, download utility, download cable and manual.	
I-7188EA	MiniOS7	Embedded Internet / Ethernet controller with 512K bytes flash, 512K bytes SRAM	
I-7188EAD	MiniOS7	I-7188EA with 7-segment LED display	V
I-7520U4	---	Isolated RS-232 to 4 Channels RS-485 Active Hub	V
I-7520U4-X	---	Isolated RS-232 to 4 Channels RS-485 Active Hub (X:The Cover is mean any color)	
I-7520U4-CA-X	---	I-7520U4-G CR with CA-0915 cable (X:The Cover is mean any color)	
I-7530	---	Intelligent RS-232 to CAN converter	V
I-7530T	---	Intelligent RS-232 to CAN converter	
I-7530-FT	---	Intelligent RS-232/CAN low speed fault tolerant converter	V
I-7530A	---	Intelligent RS-232/485/422 to CAN converter	V
I-7560	---	USB to RS-232 Converter	V
I-7563U	---	USB to Isolated RS-485 Active Star Wiring Converter	V
I-7563U-X	---	USB to Isolated RS-485 Active Star Wiring Converter (X:The Cover is mean any color)	
I-7563	---	USB to Isolated RS-485 Active Star Wiring Converter	V
I-7563-X	---	USB to Isolated RS-485 Active Star Wiring Converter (X:The Cover is mean any color)	
I-7565	---	Intelligent USB to CAN converter	V
I-7565-H1	---	High Performance Intelligent USB to 1-port CAN bus converter	V
I-7565-H2	---	High Performance Intelligent USB to 2-port CAN bus converter	V
I-8017H	---	14-bit 100K sampling rate 8-channel analog input module	V
I-8017H-X	---	14-bit 100K sampling rate 8-channel analog input module (X:The Cover is mean any color)	
I-8017HW	---	8-channel Analog Input Module	V

Main	Software	Diversity	Mode 1
I-8017HW-X	---	8-channel Analog Input Module (X:The Cover is mean any color)	
I-8024W	---	4-channel 14-bit analog output module	V
I-8024W-X	---	4-channel 14-bit analog output module (X:The Cover is mean any color)	
I-8037	---	16-channel Isolated Open Collector Output Module	V
I-8037-X	---	16-channel Isolated Open Collector Output Module (X:The Cover is mean any color)	
I-8042	---	16-channel Isolated Digital Input & 16-channel Isolated Digital Output Module	V
I-8042-X	---	16-channel Isolated Digital Input & 16-channel Isolated Digital Output Module(X:The Cover is mean any color)	
NS-208AG	---	Unmanaged 8-port 10/100/1000 Base-T Ethernet Switch with Power Input +12 VDC ~ +48 VDC	V
NSM-208AG	---	Unmanaged 8-port 10/100/1000 Base-T Ethernet Switch with Power Input +12 VDC ~ +48 VDC, metal casing	
WP-8431	Windows CE 5.0	Standard WinPAC-8000 with 4 I/O slots	V
WP-8431-EN	Windows CE 5.0	Standard WinPAC-8000 with 4 I/O slots (English verison of OS)	
WP-8436-EN	Windows CE 5.0	InduSoft and ISaGRAF based WinPAC-8000 with 4 I/O slots (English version of OS)	
WP-8437-EN	Windows CE 5.0	4 slots Ethernet WinCE 5.0 Based ISaGRAF WinPAC-8000 (OS:Multilanguage)	
WP-8439-EN	Windows CE 5.0	InduSoft based WinPAC-8000 with 4 I/O slots (English version of OS)	
WP-8431-TC	Windows CE 5.0	Standard WinPAC-8000 with 4 I/O slots (Traditional Chinese verison of OS)	
WP-8436-TC	Windows CE 5.0	InduSoft and ISaGRAF based WinPAC-8000 with 4 I/O slots (Traditional Chinese version of OS)	
WP-8437-TC	Windows CE 5.0	4 slots Ethernet WinCE 5.0 Based ISaGRAF WinPAC-8000 (OS:Traditional Chinese)	
WP-8439-TC	Windows CE 5.0	InduSoft based WinPAC-8000 with 4 I/O slots (Traditional Chinese version of OS)	
WP-8431-SC	Windows CE 5.0	Standard WinPAC-8000 with 4 I/O slots (Simplified Chinese verison of OS)	
WP-8436-SC	Windows CE 5.0	InduSoft and ISaGRAFbased WinPAC-8000 with 4 I/O slots (Simplified Chinese version of OS)	
WP-8437-SC	Windows CE 5.0	4 slots Ethernet WinCE 5.0 Based ISaGRAF WinPAC-8000 (OS:Simplified Chinese)	
WP-8439-SC	Windows CE 5.0	InduSoft based WinPAC-8000 with 4 I/O slots (Simplified Chinese version of OS)	
LP-8431-EN	Linux kernel 2.6	Standard LinPAC-8000 with 4 I/O Slots (English Version of OS)	
WP-8131	Windows CE 5.0	Standard WinPAC-8000 with 1 I/O slots	V

Main	Software	Diversity	Mode 1
WP-8131-EN	Windows CE 5.0	Standard WinPAC-8000 with 1 I/O slots (English version of OS)	
WP-8136-EN	Windows CE 5.0	InduSoft and ISaGRAF based WinPAC-8000 with 1 I/O slot (English version of OS)	
WP-8137-EN	Windows CE 5.0	1 slots Ethernet WinCE 5.0 Based ISaGRAF WinPAC-8000 (OS:Multilanguage)	
WP-8139-EN	Windows CE 5.0	InduSoft based WinPAC-8000 with 1 I/O slots (English version of OS)	
WP-8131-TC	Windows CE 5.0	Standard WinPAC-8000 with 1 I/O slots (Traditional Chinese version of OS)	
WP-8136-TC	Windows CE 5.0	InduSoft and ISaGRAF based WinPAC-8000 with 1 I/O slot (Traditional Chinese version of OS)	
WP-8137-TC	Windows CE 5.0	1 slots Ethernet WinCE 5.0 Based ISaGRAF WinPAC-8000 (Traditional Chinese)	
WP-8139-TC	Windows CE 5.0	InduSoft based WinPAC-8000 with 1 I/O slots (Traditional Chinese version of OS)	
WP-8131-SC	Windows CE 5.0	Standard WinPAC-8000 with 1 I/O slots (Simplified Chinese version of OS)	
WP-8136-SC	Windows CE 5.0	InduSoft and ISaGRAF based WinPAC-8000 with 1 I/O slot (Simplified Chinese version of OS)	
WP-8137-SC	Windows CE 5.0	1 slots Ethernet WinCE 5.0 Based ISaGRAF WinPAC-8000 (Simplified Chinese of OS)	
WP-8139-SC	Windows CE 5.0	InduSoft based WinPAC-8000 with 1 I/O slots (Simplified Chinese version of OS)	
LP-8131-EN	Linux kernel 2.6	Standard LinPAC-8000 with 1 I/O Slot (English Version of OS)	
PM-3133-100	---	Modbus RTU : 3-phase Power Meter (60 A)	V
PM-3133-160	---	Modbus RTU : 3-phase Power Meter (100 A)	
PM-3133-240	---	Modbus RTU : 3-phase Power Meter (200 A)	
PM-3133-xxxxxxx	---	Modbus RTU : 3-phase Power Meter (xxx can be 100 , 160 or 240 ; yyy can be -CAN,-CPS,-MTCP or blank)	
PDS-5105D-MTCP	---	Programmable Device Server with 10 RS-485 Ports, 2-Port Switch and LED Display	V
TP-6150	---	15" (1024 x 768) resistive touch panel monitor with RS-232 or USB interface Accessories: Power supply, VGA cable, RS-232 cable, USB cable, Mounting clamps and screws	V
TP-6150/NP	---	TP-6150 without Power supply	
uPAC-5001D-CAN2	MiniOS7	Programmable Automation controller with two series communication port (RS-232/RS-485), two CAN port, one Ethernet port, 7-segment Display, 5 programmable LEDs, 512 KB flash ,512 KB SRAM, developing tool kit, Minios7.	V
USB-2560/S	---	4-Port Industrial USB 2.0 Hub (RoHS) with GPSU06U-6 (Power Supply)	
USB-2560	---	4-Port Industrial USB 2.0 Hub (RoHS) with GPSU06U-6 (Power Supply)	V