



## FCC 47 CFR PART 15 SUBPART B

Product Type : ICP DAS Ethernet IO System  
Applicant : ICP DAS CO., LTD.  
Address : No. 111, Guangfu N. Rd., Hukou Township, Hsinchu County 30351,  
Taiwan, R.O.C.  
Trade Name : ICP DAS  
Model Number : MSM-6226 System  
Test Specification : FCC 47 CFR PART 15 SUBPART B: Oct., 2013  
ANSI C63.4: 2009  
CISPR 22: 2008  
Receive Date : Sep. 30, 2014  
Test Period : Oct. 01 2014  
Issue Date : Oct. 23, 2014

### Issue by

A Test Lab Techno Corp.  
No. 140-1, Changan Street, Bade City,  
Taoyuan County 334, Taiwan R.O.C.  
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330

**Note:** This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. This document may be altered or revised by A Test Lab Techno Corp. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, or any government agencies. The test results in the report only apply to the tested sample.

## Verification of Compliance

Issued Date: 2014/10/23

Product Type : ICP DAS Ethernet IO System

Applicant : ICP DAS CO., LTD.

Address : No. 111, Guangfu N. Rd., Hukou Township, Hsinchu County  
30351, Taiwan, R.O.C.

Trade Name : ICP DAS

Model Number : MSM-6226 System

EUT Rated Voltage : AC 100-250V, 50-60Hz, 2.0A

Test Voltage : 120 Vac / 60 Hz



Applicable : FCC 47 CFR PART 15 SUBPART B: Oct., 2013  
Standard ANSI C63.4: 2009  
CISPR 22: 2008

Test Result : Complied

Performing Lab. : A Test Lab Techno Corp.  
No. 140-1, Changan Street, Bade City,  
Taoyuan County 334, Taiwan R.O.C.  
Tel : +886-3-2710188 / Fax : +886-3-2710190  
Taiwan Accreditation Foundation accreditation number: 1330  
<http://www.atl-lab.com.tw/e-index.htm>



The above equipment has been tested by A Test Lab Techno Corp., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved By :  Reviewed By : 

(Manager) (Roy Chen) (Testing Engineer) (Frank Lin)

**Feature of Equipment under Test :**

The model listed below is series model to MSM-6226 System.

Main	Software	Diversity	Mode 1
BNET-5304	---	Multi-function BACnet/IP module with 6 AI, 1 AO, 4 DI, and 4 DO	V
ET-7024	---	Ethernet I/O Module with 4-channels AO, 5-channels DI and 5-channels DO	V
PET-7024	---	PoE Ethernet I/O Module with 4-channels AO, 5-channels DI and 5-channels DO	
ET-7224	---	Ethernet I/O Module with 2-port Ethernet Switch, with 4-channels AO, 5-channels DI and 5-channels DO	V
PET-7224	---	PoE Ethernet I/O Module with 2-port Ethernet Switch, with 4-channels AO, 5-channels DI and 5-channels DO	
EIP-2017	---	Isolated 8-ch DIFF or 16-ch SE AI EtherNet/IP Module	V
EIP-2019	---	Isolated 8-ch Thermocouple AI EtherNet/IP Module	V
EIP-2019/S	---	Isolated 8-ch Thermocouple AI EtherNet/IP Module with CN-1824 Daughter Board	
FSM-510G-4F	---	10-port GbE Managed Switch with 4-Fiber Port	V
FSM-510G-2F	---	10-port GbE Managed Switch with 2-Fiber Port	
FSM-512G-4F	---	12-port GbE Managed Switch with 4-Fiber Port	
FSM-514G-4F	---	14-port GbE Managed Switch with 4-Fiber Port	
FSM-510G	---	10-port GbE Managed Switch	
GW-7473	---	Modbus Slave to EtherNet/IP Scanner gateway with PoE and 1 RS-422/485	V
HRT-711	---	Modbus TCP to HART Gateway	V
I-2534	---	Industrial 4-port CAN bus Switch	V
I-5534-M	---	Industrial 4-port CAN bus Switch with Metal casing	
iDS-718i-D	---	Intelligent Device Server with 1 RS-232/422/485	
iDS-718iM-D	---	Intelligent Device Server with 1 RS-232/422/485 (Isolated, Metal Case, RoHS, DB9)	V
MN-3253	---	Distributed Motionnet 32-ch Isolated DI Module with RJ-45 Connector	V
MN-3253T	---	Distributed Motionnet 32-ch Isolated DI Module with Terminal Block	
MN-3257	---	Distributed Motionnet 32-ch Isolated DO Module with RJ-45 Connector	V
MN-3257T	---	Distributed Motionnet 32-ch Isolated DO Module with Terminal Block	
MSM-6226	---	24-port Ethernet + 2 TP/SFP Gigabit Dual Media Layer2 Managed Switch. (include 9-Pin Female-Female D-sub cable, 1.8 M Cable and Power Cord)	V
MSM-6226G	---	20-port 10/100/1000Base-T + 4 TP/(100/1G) SFP Combo + 2 (100/1G) SFP L2 Plus Managed Switch (9-Pin Female D-sub & RJ-45 cable, and Power Cord)	
NSM-208PSE-24V	---	8-port Industrial 10/100 Mbps Ethernet with 8-PoE (PSE) Switch	V

Main	Software	Diversity	Mode 1
NSM-208-M12	---	EN50155 8-port M12 Unmanaged Ethernet Switch	
NSM-208PSE-M12	---	EN50155 8-port M12 Unmanaged PoE Ethernet Switch	
NS-208PSE-M12-IP67	---	8-port M12 Unmanaged PoE Ethernet Switch with IP67	V
NS-208-M12-IP67	---	8-port M12 Unmanaged Ethernet Switch with IP67	
NSM-200G-SFP	---	1000Base-T to 1000Base-X Fiber SFP Media Converter	V
NSM-200SX	---	1000Base-T to 1000Base-SX Fiber Media Converter	
NSM-200SX2	---	1000Base-T to 1000Base-SX Fiber Media Converter	
NSM-200LX	---	1000Base-T to 1000Base-LX Fiber Media Converter	
NSM-200PG-SFP	---	1000Base-T to 1000Base-X Fiber SFP Media Converter with PoE	
NSM-200PSX	---	1000Base-T to 1000Base-SX Fiber Media Converter with PoE	
NSM-200PSX2	---	1000Base-T to 1000Base-SX Fiber Media Converter with PoE	
NSM-200PLX	---	1000Base-T to 1000Base-LX Fiber Media Converter with PoE	
NS-205PFT	---	Multi-mode, ST Connector, 4-port 10/100 Mbps PoE (PSE) with 1 Fiber port Switch	
NSM-205PFT	---	Multi-mode, ST Connector, 4-port 10/100 Mbps PoE (PSE) with 1 Fiber port Switch; metal case	
NS-205PFT-24V	---	Multi-mode, ST Connector, 4-port 10/100 Mbps PoE (PSE) with 1 Fiber port and 24 VDC Input Switch	V
NSM-205PFT-24V	---	Multi-mode, ST Connector, 4-port 10/100 Mbps PoE (PSE) with 1 Fiber port and 24 VDC Input Switch; metal case	
NS-205PFC	---	Multi-mode, SC Connector, 4-port 10/100 Mbps PoE (PSE) with 1 Fiber port Switch	
NSM-205PFC	---	Multi-mode, SC Connector, 4-port 10/100 Mbps PoE (PSE) with 1 Fiber port Switch; metal case	
NS-205PFC-24V	---	Multi-mode, SC Connector, 4-port 10/100 Mbps PoE (PSE) with 1 Fiber port and 24 VDC Input Switch	
NSM-205PFC-24V	---	Multi-mode, SC Connector, 4-port 10/100 Mbps PoE (PSE) with 1 Fiber port and 24 VDC Input Switch; metal case	
NS-205PFCS	---	Single-mode 30 km, SC Connector, 4-port 10/100 Mbps PoE (PSE) with 1 Fiber port Switch	
NSM-205PFCS	---	Single-mode 30 km, SC Connector, 4-port 10/100 Mbps PoE (PSE) with 1 Fiber port Switch; metal case	
NS-205PFCS-24V	---	Single-mode 30 km, SC Connector, 4-port 10/100 Mbps PoE (PSE) with 1 Fiber port and 24 VDC Input Switch	V
NSM-205PFCS-24V	---	Single-mode 30 km, SC Connector, 4-port 10/100 Mbps PoE (PSE) with 1 Fiber port and 24 VDC Input Switch; metal case	
NS-205PFCS-60	---	Single-mode 60 km, SC Connector, 4-port 10/100 Mbps PoE (PSE) with 1 Fiber port Switch	
NSM-205PFCS-60	---	Single-mode 60 km, SC Connector, 4-port 10/100 Mbps PoE (PSE) with 1 Fiber port Switch; metal case	
NS-205PFCS-60-24V	---	Single-mode 60 km, SC Connector, 4-port 10/100 Mbps PoE (PSE) with 1 Fiber port and 24 VDC Input Switch	V
NSM-205PFCS-60-24V	---	Single-mode 60 km, SC Connector, 4-port 10/100 Mbps PoE (PSE) with 1 Fiber port and 24 VDC Input Switch; metal case	

Main	Software	Diversity	Mode 1
PDS-743	---	Programmable Device Server with 3 RS-232 ports and 1 RS-485 port Includes One CA-0910 Cable	
PDSM-743	---	PDS-743 CR with Metal Case	
PDS-743D	---	Programmable Device Server with 3 RS-232 ports, 1 RS-485 port and an LED Display Includes One CA-0910 Cable	V
PDSM-743D	---	PDS-743D CR with Metal Case	
PPDS-743-MTCP	---	Programmable Device Server with PoE, Modbus Gateway, 3 RS-232 ports and 1 RS-485 port Includes One CA-0910 Cable	
PPDSM-743-MTCP	---	PPDS-743-MTCP CR with Metal Case	
PPDS-743D-MTCP	---	Programmable Device Server with PoE, Modbus Gateway, 3 RS-232 ports, 1 RS-485 port and an LED Display Includes One CA-0910 Cable	V
PPDSM-743D-MTCP	---	PPDS-743D-MTCP CR with Metal Case	
PDS-752	---	Programmable Device Server with 4 RS-232 ports and 1 RS-485 port Includes One CA-0910 Cable	
PDSM-752	---	PDS-752 CR with Metal Case	
PDS-752D	---	Programmable Device Server with 4 RS-232 ports, 1 RS-485 port and an LED Display Includes One CA-0910 Cable	V
PDSM-752D	---	PDS-752D CR with Metal Case	
PPDS-752-MTCP	---	Programmable Device Server with PoE, Modbus Gateway, 4 RS-232 ports and 1 RS-485 port Includes One CA-0910 Cable	
PPDSM-752-MTCP	---	PPDS-752-MTCP CR with Metal Case	
PPDS-752D-MTCP	---	Programmable Device Server with PoE, Modbus Gateway, 4 RS-232 ports, 1 RS-485 port and an LED Display Includes One CA-0910 Cable	V
PPDSM-752D-MTCP	---	PPDS-752D-MTCP CR with Metal Case	
PDS-755	---	Programmable Device Server with 1 RS-232 port and 4 RS-485 ports Includes One CA-0910 Cable	
PDSM-755	---	PDS-755 CR with Metal Case	
PDS-755D	---	Programmable Device Server with 1 RS-232 port, 4 RS-485 ports and an LED Display Includes One CA-0910 Cable	V
PDSM-755D	---	PDS-755D CR with Metal Case	
PPDS-755-MTCP	---	Programmable Device Server with PoE, Modbus Gateway, 1 RS-232 port and 4 RS-485 ports Includes One CA-0910 Cable	
PPDSM-755-MTCP	---	PPDS-755-MTCP CR with Metal Case	

Main	Software	Diversity	Mode 1
PPDS-755D-MTCP	---	Programmable Device Server with PoE, Modbus Gateway, 1 RS-232 port, 4 RS-485 ports and an LED Display Includes One CA-0910 Cable	V
PPDSM-755D-MTCP	---	PPDS-755D-MTCP CR with Metal Case	
PDS-762	---	Programmable Device Server with 5 RS-232 ports and 1 RS-485 port Includes One CA-0910 Cable	
PDSM-762	---	PDS-762 CR with Metal Case	
PDS-762D	---	Programmable Device Server with 5 RS-232 ports, 1 RS-485 port and an LED Display Includes One CA-0910 Cable	V
PDSM-762D	---	PDS-762D CR with Metal Case	
PPDS-762-MTCP	---	Programmable Device Server with PoE, Modbus Gateway, 5 RS-232 ports and 1 RS-485 port Includes One CA-0910 Cable	
PPDSM-762-MTCP	---	PPDS-762-MTCP CR with Metal Case	
PPDS-762D-MTCP	---	Programmable Device Server with PoE, Modbus Gateway, 5 RS-232 ports, 1 RS-485 port and an LED Display Includes One CA-0910 Cable	V
PPDSM-762D-MTCP	---	PPDS-762D-MTCP CR with Metal Case	
PDS-782	---	Programmable Device Server with 7 RS-232 ports and 1 RS-485 port Includes One CA-0910 Cable	
PDSM-782	---	PDS-782 CR with Metal Case	
PDS-782D	---	Programmable Device Server with 7 RS-232 ports, 1 RS-485 port and an LED Display Includes One CA-0910 Cable	V
PDSM-782D	---	PDS-782D CR with Metal Case	
PPDS-782-MTCP	---	Programmable Device Server with PoE, Modbus Gateway, 7 RS-232 ports and 1 RS-485 port Includes One CA-0910 Cable	
PPDSM-782-MTCP	---	PPDS-782-MTCP CR with Metal Case	
PPDS-782D-MTCP	---	Programmable Device Server with PoE, Modbus Gateway, 7 RS-232 ports, 1 RS-485 port and an LED Display Includes One CA-0910 Cable	V
PPDSM-782D-MTCP	---	PPDS-782D-MTCP CR with Metal Case	
PDS-782-25/D6	---	Programmable Device Server with 7 RS-232 ports and 1 RS-485 port Includes One CA-0910 Cable and One CA-9-2505D Cable	
PDS-782-25	---	Programmable Device Server with 7 RS-232 ports and 1 RS-485 port	
PDS-782D-25/D6	---	Programmable Device Server with 7 RS-232 ports, 1 RS-485 port and an LED Display Includes One CA-0910 Cable and One CA-9-2505D Cable	

Main	Software	Diversity	Mode 1
PDS-782D-25	---	Programmable Device Server with 7 RS-232 ports, 1 RS-485 port and an LED Display	V
PDSL-720-FOX	---	Device Server with 1 RS-232 ports and 1 RS-485 port	V
USB-2051	---	16-channel Isolated Digital Input Module	V
USB-2020	---	USB Audio Device	V
USB-2060	---	6-channel Isolated Digital Input and 6-channel Relay Output Module	V
SFP-1000SX-IT	---	Multi-mode 850 nm, 0.5 km SFP module	V
SFP-1G85M-SX	---	Multi-mode 850 nm, 0.5 km SFP module	V
SFP-1G13M-SX2	---	Multi-mode 1310 nm, 2 km SFP module	V
SFP-1G13S-LX	---	Single-mode 1310 nm, 10 km SFP module	
SFP-1G13S-LX20	---	Single-mode 1310 nm, 20 km SFP module	
SFP-1G13S-LHX	---	Single-mode 1310 nm, 40 km SFP module	
SFP-1G15S-XD	---	Single-mode 1550 nm, 60 km SFP module	

Devices Description					
Product	Manufacturer	Model Number	Serial Number	Power Cord	
(1)	Keyboard	DELL	SK-8115	MY0DJ3257161908H01 18	Power by PC
(2)	Mouse	DELL	MOC5UO	I0S02009	Power by PC
(3)	Monitor	DELL	U3214Qt	CN-0KR90-74445-3A7- 202P	Non-Shielded, 1.8m
(4)	PC	ICP DAS	BTO-AS-GI945GC	N/A	Non-Shielded, 1.8m
※ PC Keypart information					
Main	Software	Diversity		Mode 1	
(4)-1	PISO-MN200EC	---	PCI Bus, Dual-Line Motionnet Master Card		V
(4)-2	VEX-112	---	PCI Express, Serial Communication Board with 2 RS-232 ports		
(4)-3	VEX-112i	---	PCI Express, Serial Communication Board with 2 Isolated RS-232 ports		V
(4)-4	VXC-112U	---	Universal PCI Bus, Serial Communication Board with 2 RS-232 ports		
(4)-5	VXC-112AU	---	Universal PCI Bus, Serial Communication Board with 2 RS-232 ports		
(4)-6	VXC-112iAU	---	Universal PCI Bus, Serial Communication Board with 2 Isolated RS-232 ports		V

Support Unit					
Product	Manufacturer	Model Number	Serial Number	Power Cord	
1.	Industrial Power Supply	ICP DAS	DP-1200	N/A	Non-Shielded, 1.7m with one core

### 3.4. Test Site Environment

Items	Test Item	Required (IEC 60068-1)	Actual
Temperature (°C)	FCC part 15: 15.107 Conducted Emission	15-35	26
Humidity (%RH)		25-75	60
Barometric pressure (mbar)		860-1060	950
Temperature (°C)	FCC part 15: 15.109 Radiated Emission	15-35	26
Humidity (%RH)		25-75	60
Barometric pressure (mbar)		860-1060	950