



RM-38.61 Series

Relay Interface Modules 6A


RM-38.61

Features

- Relay interface modules for use with I-7000 remote I/O modules
- 6.2 mm wide, 1 pole and 35 mm rail (EN 50022) mounting
- Supplied with integral coil indication and protection circuit
- Instant removal of relay using plastic retaining clip



Relay module in i-7000 (1)



Relay module in i-7000 (2)

Specifications

Description

For PLC systems. LED and coil protection modules.
Instant removal of relay using plastic retaining clip.

Contact Specification

Contact configuration	1CO (SPDT)
Rated current (A)	6
Nominal voltage/Max voltage(V)	250/400
Rated load in AC1 (VA)	1500
Standard contact material	AgSnO2

Coil Specification


Nominal voltage	24 VDC
Rated DC power	0.17 mW

Technical Data

Insulation according to EN 61810-5	3.6 kV/3
Surge test (1.2/50µs) between coil and contacts (kV)	6 (8 mm)
Dielectric strength: open contacts (V AC)	1000
Mechanical life AC/DC (cycles)	- / 10 · 10 ⁶
Electrical life at rated load in AC1 (cycles)	60 · 10 ³
Ambient temperature range (°C)	-40...+70
Unit weight (g)	31
Boxed quantity (units)	10
Sockets	-
Accessories	-
Dimensions (mm)	76.5 x 6.5 x 89

RM-38-093.20

20-way jumper link for RM-38



Ordering Information

RM-38.61

RM-38 1CO 6A (5 piece in one box)

RM-38-093.20

20-way jumper link for RM-38