



Features :

- ICEFIN appearance, fanless design
- Desktop chassis, surface treated with shot blast and oxidation
- Intel 910GML/915GM+ICH6M chipset based, support Intel (socket 479) Pentium M/ Celeron-M processor
- 2x 100/1000Mbps Ethernet
- 1x 2.5" HDD Bay
- 4x USB2.0/1x COM/1x VGA/1x DVI/ 1x keyboard/1x mouse

Specifications

System		
Motherboard Support		MITX-6834
Display	Display Interface	1x VGA(DB15), 1x DVI-D
	Chip	Intel®910GML/915GM Integrated
	Graphic memory	Dynamic share 128MB system memory
Storage	SSD	In-built 1x CF socket (Chassis bottom), Support Type II CompactFlash
	HDD	1x 2.5" HDD Bay(In-built)
System I/O	PS/2 Port	1x Keyboard port, 1x Mouse port
	Serial Port	COM Support RS-232
	USB Port	4x USB2.0
	Audio	Line-out, Mic
	Parallel Port	N/A
Ethernet		1000Mbps, 2x RJ45
Expansion device Slot		N/A
System Control		Power Switch button, DC Input
LED Indicator		N/A
Power Supply		DC +12V
System Cooling		Fanless
OS Support		WINDOWSXP/XP-E, WINCE5.0/6.0, LINUX
Mechanical & Environmental		
Operating Temperature		0°C ~ 60°C
Storage Temperature		-40°C ~ 80°C
Relative Humidity		5% ~ 95%, 40°C, no condensing
Vibration		0.5g rms/5~500Hz/random operation
EMC		CE/FCC Class B
Dimensions		245mm×194mm×54.5mm(W×D×H)
Carton Size		330mm×272mm×152mm(W×D×H)
Net Weight		
Gross Weight		
Construction		Heavy duty steel
Surface Treat		Sand blasting and oxidation
Mounting		Desktop(Wall mounted bracket is available for this model)
Color		Black/Gold/Blue

Packing List

- **1100300409**
PSU Screw
- **0470160009**
SATA Data Cable
- **0880200009**
SATA Power Cable
- **0811500019**
Power Cord
- **1310508019**
5V@8A Power adapter
- **User's Manual**
- **Motherboard Driver CD**
- **BIS-6521**


Ordering Information

- **BIS-6521**
Embedded Box PC, support Intel (socket 479) Pentium M/ Celeron-M processor, VGA/DVI-D video output, DDR II 400/ 533MHz(up to 2GB), 1x SATA, 1x CF, 4x USB, 1x COM, 2x PS/2, 2x 1000Mbps Ethernet, Audio


Optional Accessories

- TBD

Front View




Rear View




- 1、 Power Switch
- 2、 DC +12V power input
- 3、 COM Port
- 4、 PS/2(Mouse)
- 5、 DVI Port
- 6、 2x Gigabit Ethernet
- 7、 MIC-IN
- 8、 LINE-OUT
- 9、 4x USB 2.0
- 10、 VGA Port
- 11、 PS/2(Keyboard)

Dimensions


Front View:



Side View:



Top view:



Rear View:

