

PANEL1121-841


12.1" TFT Expandable Intel® Core™2 Duo Industrial Panel Computer with 2 PCI Slots



DualView



1. SEL-
2. SEL+
3. Backlight on/off



1. COM 1 (RS-232/422/485)
2. PS/2 K/B+M/S x 2
3. COM 2/3 (RS-232)
4. VGA
5. Ethernet x 2
6. USB 2.0 x 4
7. IEEE 1394a x 2
8. Audio (Mic-in/Line-out)
9. AC power
10. Power switch
11. PCI x 2

Features

- 12.1" SVGA TFT LCD display
- Intel® Core™2 Duo processor
- Intel® Q965 + ICH8 chipset
- Expandable design: 2 PCI slots supported
- Windows® Vista and 7 supported
- Supports panel mount, wall mount, VESA arm
- Supports dimming control

Introduction

The PANEL1121-841 is a 12.1" industrial panel PC. It is equipped with 12.1" TFT LCD display and Intel® Core™2 Duo processor. The PANEL1121-841 supports Windows® Vista and adopts a PCI card for expansion capability, which is ideally suited for industrial machinery, measurement control and monitoring systems.

Powerful computing: Intel® Core™2 Duo processor

The PANEL1121-841 features Intel® Core™2 Duo processor and Intel® Q965 chipset which deliver high computing performance. The desktop CPU also offers reliability and stability for rugged environment.

Easy to expand

The PANEL1121-841 provides 2 PCI slots for easy-to-maintain purpose. Users can easily plug in standard half size PCI cards such as communication, motion and serial cards for various applications.

WLAN antenna supported (optional)

The PANEL1121-841 supports WLAN module (optional) 8 antenna for wireless network connectivity.

Specifications

Front Bezel	Aluminum w/ IP65/NEMA 4 rugged protection		Chipset	Intel® Q965 + ICH8
LCD Panel	Display Type	12.1" SVGA TFT LCD	System Memory	2 x 240-pin DDR2 DIMM max. up to 4 GB
	Brightness (cd/m ²)	370 nits	BIOS	Phoenix-Award 4Mbit with RPL/PXE LAN Boot ROM, SmartView and Customer CMOS Backup
	Resolution	800 x 600 pixels	Storage	1 x 2.5" SATA HDD
	Viewing Angle (H/V)	120° / 140°	Watchdog Timer	255 levels, 1-255 sec.
Main system	CPU	LGA775 for Intel® Core™2 Duo/ Core™ Solo processor with FSB 533/800/ 1066 MHz		

I/O Connector	2 x RS-232 (COM 2/3) 1 x RS-232/422/485 (COM 1) 2 x IEEE 1394a 4 x USB 2.0 2 x PS/2 keyboard/mouse 2 x 10/100/1000Mbps Ethernet 1 x Audio (Line-out/Mic-in) 1 x DVI-I (female) for display (a converter for DVI-I to VGA is included)
Expansion Interface	2 x PCI slot
Touch screen	Resistive type Light Transmission 79% 1 million activations (typical) at a single point
Power supply	100 – 240V _{AC} , 250W
Dimensions	340 mm (13.39") (W) x 120 mm (4.73") (D) x 272 mm (10.7") (H)
Packing Dimensions	510 mm (20.08") (W) x 190 mm (7.48") (D) x 540 mm (21.26") (H)
Weight (net/gross)	6.3 kg (13.9 lb)/8.4 kg (18.5 lb)
Environment	Operating temperature: 0° C ~ +40° C (32° - 104° F) Relative humidity: 10 - 95%@40° C, non-condensing Operation vibration: 1.0G,5-500Hz, random
Certification	CE

Ordering Information

P1121-841	12.1" SVGA TFT LGA775 socket Intel® Core™2 Duo industrial panel PC with 2 PCI slots
-----------	---

* Specification and certifications are based on options and may vary.
** PANEL1xxx is commonly known as P1xxx.

Optional Accessories

E202003330	VM-101 (VESA ARM clamp type)
E202003329	VM-105 (VESA ARM wallmount)
82211530110E	Wireless LAN kit
82211210060E	PANEL1121-841 VESA kit

Optional OS Installation

Windows® XP/Vista/7

Overview

Industrial Panel Computers & Monitors

Heavy-duty Fanless Touch Panel Computers

Digital Signage Solutions

Healthcare & Medical Solutions

Open Frame Panel Computers

Accessories

Dimensions

