
PANEL1173-841

17" TFT Expandable Intel® Core™2 Duo Industrial Panel Computer with 2 PCI Slots



Introduction

The PANEL1173-841 is a 17" industrial panel PC which features Intel[®] Core [™]2 Duo processor and Intel[®] Q965 chipset to provide powerful computing performance. This panel PC also offers the expansion ability with 2 PCI slots. Further, the PANEL1173-841 adopts built-in speaker and WLAN module for wireless connectivity.

Powerful computing: Intel[®] Core[™]2 Duo processor

The PANEL1173-841 features Intel® Core™2 Duo with maximum FSB 1066 MHz and Intel® Q965+ICH8 chipset. It features two IEEE 1394a ports, two gigabit Ethernet and up to 4GB of dual-channel DDR2 system memory which deliver high computing capability for high performance-demanding applications.

Expandable for 2 PCI slots

The PANEL1173-841 has 2 PCI slots for expansion purpose. User can easily plug in standard half-size PCI cards such as motion card, communication card and so on.

Speaker & WLAN antenna supported

The PANEL1173-841 features built-in speaker, optional WLAN module and antenna for wireless network connectivity.

Specifications

| Front Bezel | Industrial-grade material with IP65/NEMA 4 rugged protection | | Chipset | Intel [®] Q965 + ICH8 | |
|-------------|--|--|----------------|---------------------------------------|--|
| LCD Panel | Display Type | 17" SXGA TFT | System Memory | 2 x 240-pin DDR2 DIMM max. up to 4 GB | |
| | Brightness (cd/m ²) | 380 nits | BIOS | Phoenix-Award 4Mbit with RPL/PXE LAN | |
| | Resolution | 1280 x 1024 pixels | | Boot ROM, SmartView and customer | |
| | View Angle (H/V) | 120°/140° | | CMOS backup | |
| Main system | CPU | LGA775 for Intel [®] Core™2 Duo/ Core™ Solo | Storage | 2 x 3.5" or 2 x 2.5" SATA HDD | |
| | | processor with FSB 533/667/800/1066 MHz | Drive | 1 x slim CD-ROM | |
| | | | Watchdog Timer | 255 levels, 1~255 sec. | |

| IO connector | 2 x RS-232 (COM 2/3) 1 x RS-232/422/485 (COM 1) 2 x IEEE 1394a 4 x USB 2.0 2 x P5/2 keyboard/mouse 2 x 10/100/1000Mbps Ethernet 1 x DVI-I for display (a converter for DVI-I to VGA is included) 1 x Audio (Mic-in/Line-out) |
|------------------------|--|
| Expansion Interface | 2 x PCI slot |
| Touchscreen | Resistive type Light Transmission 79% 1 million activations (typical) at a single point |
| Power supply | 100 ~ 240V _{AC} , 250W |
| Dimensions | 450 mm (17.71") (W) x 150 mm (5.9") (D) x 370 mm (14.56") (H) |
| Packing Dimensions | 610 mm (24.02") (W) x 260 mm (10.24") (D) x 590 mm (23.23") (H) |
| Weight (net/gross) | 7.5 kg (16.5 lb)/11.3 kg (24.9 lb) |
| Environment | Operating temperature: 0° - +40°C (32° - 104°F) Relative humidity: 10 - 95% @ 40°C, non-condensing Operation vibration: 1.0G, 5-500Hz, random |
| Certification | CE |

Ordering Information

| P1173-841 | 17" SXGA TFT LGA775 socket Intel® Core™2 Duo panel PC with 2 PCI slots |
|--------------------|---|
| * Specification an | d certifications are based on options and may vary. |
| ** DANEL toos is a | ommonly known as P1xxx. |

Optional Accessories

| 82211730040E | 2 x 3.5" HDD kit | |
|--------------|------------------|----------|
| 82011750130E | 2 x 2.5" HDD kit | botación |
| 82011750110E | Rack mount kit | |
| 82211530110E | Wireless LAN kit | |

Optional OS Installation

Windows[®] 2000/XP/Vista

Overview

Industrial Panel Computers & Monitors

Heavy-duty Fanle Touch Panel Computers

> Digital Signage Solutions

> > Healthcare & Medical Solutions

Open Frame Panel Computer

Accessories

Dimensions

