



FCC 47 CFR PART 15 SUBPART B

Product Type : ICP DAS IO System
Applicant : ICP DAS CO., LTD.
Address : No. 111, Guangfu N. Rd., Hukou Township, Hsinchu County 30351,
Taiwan, R.O.C.
Trade Name : ICP DAS
Model Number : FSM-6228G System
Test Specification : FCC 47 CFR PART 15 SUBPART B: Oct., 2013
ANSI C63.4: 2009
CISPR 22: 2008
Receive Date : Nov. 06, 2014
Test Period : Nov. 10 ~ 13, 2014
Issue Date : Dec. 01, 2014

Issue by

A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade City,
Taoyuan County 334, Taiwan R.O.C.
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330

Note: This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. This document may be altered or revised by A Test Lab Techno Corp. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, or any government agencies. The test results in the report only apply to the tested sample.

Verification of Compliance

Issued Date: 2014/12/01

Product Type : ICP DAS IO System
Applicant : ICP DAS CO., LTD.
Address : No. 111, Guangfu N. Rd., Hukou Township, Hsinchu County
30351, Taiwan, R.O.C.
Trade Name : ICP DAS
Model Number : FSM-6228G System
EUT Rated Voltage : AC 100-250V, 50-60Hz, 2.0A
Test Voltage : 120 Vac / 60 Hz
Applicable : FCC 47 CFR PART 15 SUBPART B: Oct., 2013
Standard : ANSI C63.4: 2009
CISPR 22: 2008
Test Result : Complied
Performing Lab. : A Test Lab Techno Corp.

No. 140-1, Changan Street, Bade City,
Taoyuan County 334, Taiwan R.O.C.



Tel : +886-3-2710188 / Fax : +886-3-2710190

Taiwan Accreditation Foundation accreditation number: 1330

<http://www.atl-lab.com.tw/e-index.htm>



The above equipment has been tested by A Test Lab Techno Corp., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved By :  Reviewed By : 
(Manager) (Roy Chen) (Testing Engineer) (Frank Lin)

2 EUT Description

Product Type	:	ICP DAS IO System
Trade Name	:	ICP DAS
Model Number	:	FSM-6228G System
Applicant	:	ICP DAS CO., LTD. No. 111, Guangfu N. Rd., Hukou Township, Hsinchu County 30351, Taiwan, R.O.C.
Manufacturer	:	ICP DAS CO., LTD. No. 111, Guangfu N. Rd., Hukou Township, Hsinchu County 30351, Taiwan, R.O.C.

I/O Port Description :

I/O Port Types	Q'TY	Test Description
1). AC Power Port	1	Connected to EUT
2). AC Power Port	1	Connected to AC input
3). LAN Port	1	Connected to PC
4). USB Port	1	Connected to PC
5). LAN Port	1	Connected to EUT
6). DC Power Port	1	Connected to EUT

Feature of Equipment under Test :

The model listed below is series model to FSM-6228G System.

Main	Software	Diversity	Mode 1
WF-2017	---	8-channel Differential/16-channel Single-Ended Analog Input Wi-Fi I/O Module	V
WF-2051	---	Wi-Fi I/O Module with 16-channel Isolated Digital Input	V
WF-2042	---	Wi-Fi I/O Module with 16-channel Isolated Digital Output	V
WF-2026	---	5-channel Analog Input, 2-channel Analog Output, 2-channel Digital Input and 3-channel Digital Output Wi-Fi I/O Module	V
WF-2019	---	10-channel Universal Analog Input Wi-Fi I/O Module	V
WF-2019/S	---	10-channel Universal Analog Input Wi-Fi I/O Module with DB-1820 Daughter Board	
RMV-531	---	Intelligent Multiport Serial to 2G/3G Gateway	V
GRP-520	---	3G Gateway	V
RMV-514	---	Intelligent Multiport Serial to GPRS Gateway with I/O	V
RMV-512	---	Intelligent Multiport Serial to GPRS Gateway with I/O	
SC-4104-W1	---	1-channel AC Digital Input and 4-channel Relay Output Lighting Control Module	V
I-7043	---	16-channel Non-isolated Digital Output Module using the DCON Protocol	V
I-7043-X	---	16-channel Non-isolated Digital Output Module using the DCON Protocol (X : The Cover is mean any color)	
I-7043D	---	I-7043 with LED Display	
I-7043D-X	---	I-7043 with LED Display (X : The Cover is mean any color)	
M-7043-X	---	16-channel Non-isolated Digital Output Module using the DCON and Modbus Protocol (X : The Cover is mean any color)	
M-7043	---	16-channel Non-isolated Digital Output Module using the DCON and Modbus Protocol	
M-7043D-X	---	M-7043 with LED Display (X : The Cover is mean any color)	
M-7043D	---	M-7043 with LED Display	
WISE-7901	MiniOS7	User-defined I/O Expansion PoE Module	
WISE-7901D	MiniOS7	User-defined I/O Expansion PoE Module with LED Display	V
uPAC-7186PEX	MiniOS7	Palm-size μ PAC with PoE	
uPAC-7186PEXD	MiniOS7	uPAC-7186PEX with 7 segment LED display	
uPAC-7186PEX-MTCP	MiniOS7	uPAC-7186PEX with default Modbus/TCP firmware	
uPAC-7186PEXD-MTCP	MiniOS7	uPAC-7186PEXD with default Modbus/TCP firmware	
PDS-720	MiniOS7	Programmable Device Server with 1 RS-232 port and 1 RS-485 port Includes One CA-0910 Cable	

Main	Software	Diversity	Mode 1
PDS-720D	MiniOS7	Programmable Device Server with 1 RS-232 port, 1 RS-485 port and an LED Display Includes One CA-0910 Cable	
PPDS-720-MTCP	MiniOS7	Programmable Device Server with PoE, Modbus Gateway, 1 RS-232 port and 1 RS-485 port Includes One CA-0910 Cable	
PPDS-720D-MTCP	MiniOS7	Programmable Device Server with PoE, Modbus Gateway, 1 RS-232 port, 1 RS-485 port and an LED Display Includes One CA-0910 Cable	
MDC-711	MiniOS7	Modbus Data Concentrator	
MDC-714	MiniOS7	Modbus Data Concentrator with 4-port RS-485	
M2M-710D	MiniOS7	Remote maintenance Ethernet Device Terminal Unit	
I-7590	---	RS-232 / RS-422 / RS-485 to M-Bus Converter	V
USB-2045	---	16 Source-type Digital Output Channels with Overload Protection	V
USB-2055	---	8-channel Isolated Digital Input and 8-channel Isolated Digital Output	V
USB-2051	---	16-channel Isolated Digital Input Module	V
USB-2060	---	6-channel Isolated Digital Input and 6-channel Relay Output Module	V
uPAC-5201D-FD	MiniOS7	uPAC-5000 with LAN and 2G (GPRS) and 256 MB Flash	
uPAC-5201-FD	MiniOS7	uPAC-5000 with LAN and 2G (GPRS) and 256 MB Flash	V
uPAC-5201D	MiniOS7	uPAC-5000 with LAN and 2G (GPRS)	
uPAC-5201	MiniOS7	uPAC-5000 with LAN and 2G (GPRS)	
uPAC-5202D-FD	MiniOS7	uPAC-5000 with LAN and 2G (GPRS) and 256 MB Flash (ISaGRAF)	
uPAC-5202-FD	MiniOS7	uPAC-5000 with LAN and 2G (GPRS) and 256 MB Flash (ISaGRAF)	
uPAC-5202D	MiniOS7	uPAC-5000 with LAN and 2G (GPRS) (ISaGRAF)	
uPAC-5202	MiniOS7	uPAC-5000 with LAN and 2G (GPRS) (ISaGRAF)	
uPAC-5207D	MiniOS7	uPAC-5000 with LAN and 2G (GPRS) (ISaGRAF)	
uPAC-5207	MiniOS7	uPAC-5000 with LAN and 2G (GPRS) (ISaGRAF)	
uPAC-5002	MiniOS7	uPAC-5000 with LAN	
uPAC-5002D	MiniOS7	uPAC-5000 with LAN	
uPAC-5002-FD	MiniOS7	uPAC-5000 with LAN and 256 MB Flash	
uPAC-5002D-FD	MiniOS7	uPAC-5000 with LAN and 256 MB Flash	
uPAC-5002-SM	MiniOS7	uPAC-5000 with LAN	
uPAC-5002D-SM	MiniOS7	uPAC-5000 with LAN	
uPAC-5007	MiniOS7	ISaGRAF based μ PAC-5000 with LAN	
uPAC-5007D	MiniOS7	ISaGRAF based μ PAC-5000 with LAN	
uPAC-5001	MiniOS7	uPAC-5000 with LAN	

Main	Software	Diversity	Mode 1
uPAC-5001D	MiniOS7	uPAC-5000 with LAN	
uPAC-5001-FD	MiniOS7	uPAC-5000 with LAN and 256 MB Flash	
uPAC-5001D-FD	MiniOS7	uPAC-5000 with LAN and 256 MB Flash	
ECAT-2045	---	EtherCAT Slave I/O Module with Isolated 16-ch Digital Outputs	V
ECAT-2055	---	EtherCAT Slave I/O Module with Isolated 8-ch DO and 8-ch DI	V
ECAT-2051	---	EtherCAT Slave I/O Module with Isolated 16-ch Digital Inputs	V
PDS-842	---	Programmable Device Server with 4 Expansion Slots	
PDS-882	---	Programmable Device Server with 8 Expansion Slots	V
I-8040W-X	---	32-channel Isolated Digital Input Module (X : The Cover is mean any color)	
I-8040W	---	32-channel Isolated Digital Input Module	
I-8040W-A1-X	---	32-channel Isolated Digital Input Module (X : The Cover is mean any color)	
I-8040W-A1	---	32-channel Isolated Digital Input Module	
I-8040W-A2-X	---	32-channel Isolated Digital Input Module (X : The Cover is mean any color)	
I-8040W-A2	---	32-channel Isolated Digital Input Module	V
I-8112-X	---	2-Port RS-232 Module (X : The Cover is mean any color)	
I-8112	---	2-Port RS-232 Module	V
I-8080-X	---	4/8-channel Counter/Frequency Module (X : The Cover is mean any color)	
I-8080	---	4/8-channel Counter/Frequency Module	V
I-8084W-X	---	4/8-channel Counter/Frequency/Encoder Module (X : The Cover is mean any color)	
I-8084W	---	4/8-channel Counter/Frequency/Encoder Module	V
I-8088W-X	---	8-channel PWM Output And 8-Channel isolated DI Module (X : The Cover is mean any color)	
I-8088W	---	8-channel PWM Output And 8-Channel isolated DI Module	V
I-8090-X	---	3-axis Encoder Module (X : The Cover is mean any color)	
I-8090	---	3-axis Encoder Module	V
I-8091-X	---	2-axis Stepping/Servo Motor Control Card (X : The Cover is mean any color)	
I-8091	---	2-axis Stepping/Servo Motor Control Card	V
PFN-2052	---	PROFINET I/O Module (Isolated 8-ch DI)	V
PFN-2053	---	PROFINET I/O Module (Dry contact Non-Isolated 16-ch DI)	V
EIP-2017	---	Isolated 8-ch DIFF or 16-ch SE AI EtherNet/IP Module	V
EIP-2019	---	Isolated 8-ch Thermocouple AI EtherNet/IP Module	V
EIP-2019/S	---	Isolated 8-ch Thermocouple AI EtherNet/IP Module with CN-1824 Daughter Board	

Main	Software	Diversity	Mode 1
FSM-6228G	---	24-port 10/100/1000Base-T + 4 (100/1G) SFP L2 Managed Switch	V
FSM-6228G-DC	---	24-port 10/100/1000Base-T + 4 (100/1G) SFP L2 Managed Switch (Dual Power, DC/AC Input)	
FSM-6228G-AC	---	24-port 10/100/1000Base-T + 4 (100/1G) SFP L2 Managed Switch (AC Input)	
PPDS-741-IP67	---	Programmable Device Server with 1 RS-232 port, 3 RS-485 ports, PoE and IP67 Casing	
PPDS-742-IP67	---	Programmable Device Server with 2 RS-232 ports, 2 RS-485 ports, PoE and IP67 Casing	V
PPDS-743-IP67	---	Programmable Device Server with 3 RS-232 ports, 1 RS-485 port, PoE and IP67 Casing	

Devices Description					
Product		Manufacturer	Model Number	Serial Number	Power Cord
(1)	Keyboard	DELL	SK-8110	07N2443884232J7Q39	Power by PC
(2)	Mouse	DELL	MO71KC	511091717	Power by PC
(3)	Monitor	DELL	U3011t	CN-0PH5NY-74445-1A 8-092L	Non-Shielded, 1.8m
(4)	PC	ICP DAS	BTO-AS-GI945GC	N/A	Non-Shielded, 1.8m
※ PC Keypart information					
Main		Software	Diversity		Mode 1
(4)-1	PCI-1802LU	---	Universal PCI, 32-ch, 12-bit, 330 kS/s Low Gain Multi-function DAQ Board (8 K word FIFO) Includes one CA-4002 D-Sub connector.		V
(4)-2	PCI-1802HU	---	Universal PCI, 2-ch, 12-bit, 40 kS/s High Gain Multi-function DAQ Board (8 K word FIFO) Includes one CA-4002 D-Sub connector		
(4)-3	PCI-1802HU/S	---	PCI-1802HU CR with DB-1825 daughter board, Cable Includes one CA-3710 D-Sub cable.		
(4)-4	PCI-1802LU/S	---	PCI-1802LU CR with DB-1825 daughter board, Cable Includes one CA-3710 D-Sub cable.		
(4)-5	VXC-114iAU	---	Universal PCI, Serial Communication Board with 4 Isolated RS-232 ports Includes One CA-4002 Connector		V
(4)-6	VXC-114iAU/D2	---	Universal PCI, Serial Communication Board with 4 Isolated RS-232 ports Includes One CA-9-3715D Cable		
(4)-7	PCI-1002HU	---	Universal PCI, 32-ch, 12-bit, 44 kS/s High Gain Multi-function DAQ Board Includes one CA-4002 D-Sub connector.		
(4)-8	PCI-1002HU/S	---	Universal PCI, PCI-1002HU with DB-1825 daughter board , Cable Includes one CA-3710 D-Sub cable.		
(4)-9	PCI-1002LU	---	Universal PCI, 32-ch, 12-bit, 110 kS/s Low Gain Multi-function DAQ Board Includes one CA-4002 D-Sub connector.		V
(4)-10	PCI-1002LU/S	---	Universal PCI, PCI-1002LU with DB-1825 daughter board, Cable Includes one CA-3710 D-Sub cable.		
(4)-11	PISO-DA4U	---	Universal PCI 4-channel isolated D/A board Includes one CA-4002 D-Sub connector.		
(4)-12	PISO-DA4U/S	---	PISO-DA4U with DN-37 Includes one CA-3710 D-Sub cable.		
(4)-13	PISO-DA8U	---	Universal PCI 8-channel isolated D/A board Includes one CA-4002 D-Sub connector.		
(4)-14	PISO-DA8U/S	---	PISO-DA8U with DN-37 Includes one CA-3710 D-Sub cable.		
(4)-15	PISO-DA16U	---	Universal PCI 16-channel isolated D/A board Includes one CA-4002 D-Sub connector.		V
(4)-16	PISO-DA16U/S	---	PISO-DA16U with DN-37 Includes one CA-3710 D-Sub cable.		

Support Unit					
Product		Manufacturer	Model Number	Serial Number	Power Cord
1.	Industrial Power Supply	ICP DAS	DP-1200	N/A	Non-Shielded, 1.7m with one core