

## CERTIFICATE

## of conformity

Order No. EC6N2310

Type of equipment: MAVIS

Document holder: ICP DAS CO., LTD.

No. 111, Kuangfu N. Rd., Hukou Shiang, Hsinchu, Taiwan

303, R.O.C.

Type designation: Appendix 1 to Order No. EC6N2310

Technical data: Class A device Trade name: ICPDAS

A sample of the equipment was tested and evaluated and found to comply with the following standard(s):

Standard(s):

EN 55022:1998/A1: 2000/A2: 2003 Class A

EN55024: 1998/A1: 2001/A2: 2003

The equipment covered by this document is subject to mandatory compliance with - the EMC Directive 89/336/EEC.

Compliance with the standards listed above give presumption of conformity with the technical requirements of the directive they are harmonized to. Additional requirements may apply before placing on the market is legal e.g. Declaration of Conformity, the CE marking, technical documentation prepared/filed/updated and factory quality control.

The work performed by the laboratory issuing this document is covered in the scope of her accreditation by CNLA. The documents shall be read in conjunction with the full test report(s). No follow up or inspection service is implied in this document and no period of validity is applicable.

Additional information in Appendix 1

Dec. 04, 2006 Sporton International Inc.

Elton Chen / Manager



## Appendix 1 to Order No. EC6N2310

## **Additional Information**

Regarding to the difference construction of the EUT, the model number were shown in the table as following:

**Model Number Main Control Unit Diversity** IEEE 1394 Digital Camera (640 x 480, Monochrome, 30fps, Lens IOI-4601 IM30 not included) IEEE 1394 Digital Camera (640 x 480, Monochrome, 100fps, Lens IM100 not included) 45ks/s Low gain 12-bit,16-channel input , 1-channel D/A, Digital PIO-821L/H PIO-821L 45ks/s Low gain 12-bit,16-channel input , 1-channel D/A, Digital PIO-821H PISO-PS400 PISO-PS400 High Speed 4-Axes Motion Control Module Photo-isolated terminal board for four-axis stepper/servo DN-8468 controller A-812PG A-812PG 62.5KS/s 12-bit Analog & Digital I/O Board Daughter Board for A-82x Series, PCI-1800 with 1 M D-sub 37-pin DB-8225 Cable ISO-DA8 ISO-DA8 14-bit of 8-channel Isolated Analog Output Board 32-bit Digital Input and 32-bit Digital Output, 3 Timer/Counter DIO-64/3 DIO-64/3 Board 16-channel Opto-islated Digital Input & 8-channel Relay Output DB-16P8R Board

Note: PIO-821L and PIO-821H are identical in hardware specification except