

SER5037A

2-port RS-232 Universal PCI
Serial Board



Introduction

SUNIX SER5037A, Universal PCI serial communication board, allows users to add or expand two RS-232 ports on PC-based system. The card is compatible with both 64 / 32-bit PCI architecture supporting 3.3 and 5V Bus, allowing it to be installed in virtually any PC-based systems. SUNIX SER5037A card has 128-bytes onboard FIFO buffer and compatible with 16C950 UART specification. It is designed with SUNIX UART controller, SUN1989 and as well built with many of SUNIX advanced features and technologies, making it the best solution for commercial and industrial automation applications.

Features

- Expands 2 independent RS-232 serial ports with communication speeds up to 115.2Kbps.
- High speed SUN1989 16C950 compatible UART controller on-board.
- Compliance with PCI 33MHz Ver. 3.0/2.3/2.2./2.1 specification.
- Supports both 64-bit & 32-bit PCI bus slot and 3.3V & 5V power.
- On-chip hardware auto flow control to guarantee no data loss.
- Built-in ± 2 KV ESD protection for all serial signals.
- Plug-n-Play, I/O address and IRQ assigned by BIOS.
- Certified by CE, FCC, RoHS, and Microsoft WHQL approval.
- Support Microsoft Windows, Linux, and DOS.



Specifications

Serial Communication

Interface	RS-232	Signal	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND, RI
Controller	SUNIX SUN1989 (16C950 UART Compatible)	Baud rate	50bps ~115.2Kbps
BUS	Universal PCI 64/32bit 3.3V/5V PCI Ver 3.0, 2.3, 2.2, 2.1	Stop bit	1, 1.5, 2
No. of Port	2-port	Parity	even, odd, none, mark, space
IRQ & IO	Assigned by System	Flow Control	None, Xon/Xoff, RTS/CTS
FIFO	128byte Hardware	PCB Connector	DB9 Male
Protection	±2KV ESD protection for each signal Human Body Model (HBM)		

Driver Support

Microsoft Client	Windows XP/Vista/7 (X86/X64)
Microsoft Server	Windows 2000/2003/2008 (X86/X64)
Microsoft Embedded	Windows CE5.0/6.0/XP Embedded/POS Ready 2009/Embedded System 2009
Linux	Linux 2.4.x/2.6.x
DOS	DOS
FreeBSD	FreeBSD 5.3~5.5 / 6.0~6.4
QNX	QNX 6.3.2/6.4.0
* IBM OS/2	WARP 3/WARP 4
* SCO UnixWare	UnixWare 7.1.3/7.1.4/ Open Server 5.0.7/6.0
* Sun Microsystems	Solaris 10
Note : " * " Supported by special inquiry.	

Regulatory Approvals

Hardware	EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, FCC Part 15 Class B, BSMI: CNS13438, C-Tick: CISPR22 AS/NZS, RoHS
Software	Microsoft WHQL Windows ◆ Microsoft Client: XP/Vista/7 (X86/X64) ◆ Microsoft Server: 2000/2003/2008 (X86/X64)


Environment

Operation Temperature	0 to 60°C (32 to 140°F)
Operation Humidity	5 to 95% RH
Storage Temperature	-20 to 85°C (-4 to 185°F)


Dimension

PCB Dimension	120 x 82 mm
Bracket	Standard 121 mm
Bracket Space	1


Application



Mechanical Drawings (Unit = mm)



Pin Assignment



PIN	DB9M
DCD	1
RxD	2
TxD	3
DTR	4
GND	5
DSR	6
RTS	7
CTS	8
RI	9



Packing List

Packing Content

- SER5037A – 2-port RS-232 Universal PCI Serial Board
- Quick Installation Guide
- Software CD ROM



Order Information

Serial RS-232 Interface

Bus	Port	Connector	Baud Rate	ESD Protection	Power output	Bracket	Model NO.	
PCI Express	8	DB62 Female	115.2 kbps	±15KV	-	Standard	SER5466A	
			921.6Kbps		-		SER5466H	
		Mini SCSI 68 Female	115.2 kbps		-	Low profile	SER5466AL	
			921.6Kbps		-		SER5466HL	
	4	DB44 Female	115.2 kbps		-	Standard	SER5456A	
					5V/12V		-	SER5456P
			921.6Kbps		-	Low profile	SER5456AL	
					5V/12V		-	SER5456PL
		DB9 Male	115.2 kbps		-	Standard	SER5456H	
					5V/12V		-	SER5456PH
			921.6Kbps		-	Low profile	SER5456HL	
					5V/12V		-	SER5456PHL
	2	DB9 Male	115.2 kbps		-	Standard	SER5437A	
					5V/12V		-	SER5437P
		DB44 Female	921.6Kbps		-	Low profile	SER5437AL	
					5V/12V		-	SER5437PL
		DB9 Male	921.6Kbps		-	Standard	SER5437H	
					5V/12V		-	SER5437PH
DB44 Female	921.6Kbps	-	Low profile	SER5437HL				
		5V/12V		-	SER5437PHL			
PCI	8	DB62 Female	115.2 Kbps	±2KV	-	Standard	SER5066A	
					Mini SCSI 68 Female		-	SER5066AL
		5x2 Pin Header			-	Low profile	SER5066U	
					-		SER5066UL	
		DB62 Female			921.6Kbps	-	Standard	SER5066H
						Mini SCSI 68 female		-
	5x2 Pin Header	-	Low profile	SER5066UH				
		-		SER5066UHL				
	4	DB44 Female	115.2 Kbps	±2KV		-	Standard	SER5056A
						5V/12V		-
		5x2 Pin Header			-	Low profile	SER5056AL	
					5V/12V		-	SER5056PL
		DB44 Female			921.6Kbps	-	Standard	SER5056U
						-		SER5056UL
	5x2 Pin Header	-	Low profile	SER5056H				
		-		SER5056HL				
	DB44 Female	921.6Kbps	-	Standard		SER5056PH		
			5V/12V			-	SER5056PUH	
	5x2 Pin Header		-	Low profile	SER5056UH			
			-		SER5056UHL			
	DB44 Female		921.6Kbps	-	Standard	SER5056PHL		
				5V/12V		-	SER5056PHL	
	2	DB9 Male		115.2Kbps	±2KV	-	Standard	SER5037A
						5V/12V		-
		5x2 Pin Header				-	Low profile	SER5037U
						-		SER5037AL
		DB44 Female	921.6Kbps			-	Standard	SER5037PH
						5V/12V		-
	5x2 Pin Header	-		Low profile	SER5037UL			
		-			SER5037UL			
	DB9 Male	921.6Kbps		-	Standard	SER5037H		
				5V/12V		-	SER5037PH	
	5x2 Pin Header		-	Low profile	SER5037UH			
			-		SER5037HL			
	DB44 Female		921.6Kbps	-	Standard	SER5037PHL		
				5V/12V		-	SER5037PHL	
1	DB9 Male	115.2Kbps		±2KV	-	Standard	SER5027A	
					5V/12V		-	SER5027P
	5x2 Pin Header				-	Low profile	SER5027U	
					-		SER5027AL	
	DB9 Male		921.6Kbps		-	Standard	SER5027PH	
					5V/12V		-	SER5027PH
5x2 Pin Header	-	Low profile		SER5027UL				
	-			SER5027UL				
DB9 Male	921.6Kbps	-		Standard	SER5027H			
		5V/12V			-	SER5027PH		
5x2 Pin Header		-	Low profile	SER5027UH				
		-		SER5027HL				
DB9 Male		921.6Kbps	-	Standard	SER5027PHL			
			5V/12V		-	SER5027PHL		
Express Card	4		DB44 Female	921.6Kbps	±15KV	-	34mm	ECS4000
	2					-	34mm	ECS2000
	1					DB9 Male	-	34mm
CardBus	4		DB44 Female	115.2Kbps	±15KV	-	54mm	CBS4000
	2	-				54mm	CBS2000	
	1	DB9 Male				-	54mm	CBS1000